

## **Type HAGOlifter HL** The convenient lifter





1 Screw in the delivered fixing screws.



2 Simply operate the crank and the manhole cover will be lifted.



3 Roll the manhole cover to the side.

## **Recommended applications:**

The **HAGOlifter** is most suitable for **HAGO** manhole covers without hinge. With this convenient lifter the lifting of manhole covers becomes child's play.

Even heavy covers can be lifted and moved to the side by just one person and without any particular efforts.

## **Scope of delivery:**

The **HAGOlifter** is delivered as a complete set consisting of:

- 2 pcs. Lifting unit (painted red) with aluminium wheels and rubber tyres
- 2 pcs. Fixing screws M10 (for HAGO manhole covers made of aluminium)
- 2 pcs. Fixing screws M12 (for HAGO manhole covers made of galvanized and stainless steel)
- 2 pcs. Rubber protection plates (to place on sensitive floors)



After use the fixing screws and the rubber protection plates can be fastened to the lifter. So nothing can be lost for the next use.

Туре	Lifting height	Weight of one lifting unit
HAGOlifter HL-26	26 cm	11 kg

Also available in special design HAGOlifter HL-31 **XH** (extra high) with extended lifting height (31 cm).

The design HL-31 XH is only required for the manhole cover BV(E)HS 400/110 (concerns only size 100 x 100 cm) or for the particularly high HAGO special covers.